



Description: Hardline Connector, B071-5/8 male.

GENERIC DATA SHEET

Electrical

	Specification		Standard
Frequency Range	5 MHz – 3.000 MHz		
Impedance	75 Ω nominal		
	Better Than	Measured – Worst case of 5 measurements	
Return Loss Gated	31 dB	≥ 34 dB	IEC 61169-1
	29 dB	≥ 32 dB	
	28 dB	≥ 31 dB	
	26 dB	≥ 29 dB	
	26 dB	≥ 29 dB	
	26 dB	≥ 29 dB	
	28 dB	≥ 31 dB	
Insertion Loss	0.13 dB	≤ 0.10 dB	5 MHz – 3.000 MHz
Shielding Effectiveness	Transfer Impedance @ 5 – 30 MHz		IEC 62153-4-3
	Screening Attenuation @ 30 – 1.000 MHz		IEC 62153-4-4
	Screening Attenuation @ 1.000 – 2.000 MHz		IEC 62153-4-4
	Screening Attenuation @ 2.000 – 3.000 MHz		IEC 62153-4-4
	Class: A++		EN 50117
Common Path Distortion	≤ -110 dBc		ANSI/SCTE 109 2005
Inner Conductor Resistance	≤ 2.5 mΩ @ 1 A DC.		IEC 61169-1
Amp. Rating	≤ 15 A @ 60 V.		
Dielectric Strength	≥ 3 kV.		IEC 61169-1
Insulation Resistance	≥ 29.99 GΩ @ 500 V.		IEC 61169-1

Environmental

	Specification	Standard
Temperature range Operating	-40°C to +65°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Red Dye		ANSI/SCTE 60
Corrosion Protection		ASTM B 117-94

Mechanical

	Specification	Standard
Interface	5/8 male	ANSI/SCTE 92
Cable Retention	≥ 30 kgf	ANSI/SCTE 99

Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass	ASTM B605
Compression ring	NiSn (NITIN) plated Brass	ASTM B605
O'ring	EPDM	
Insulator	Polycarbonate/Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

All results are the worst case result of measurement of 5 assemblies.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current (≥ 15 A.) there is a risk for high temperature inside the connector, which can cause damage of the insulator, and / or the cable.

Further test reports, technical specifications and installation instructions can be obtained on request.

